SAFETY DATA SHEET According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Material: 60133508 **WACKER® PRIMER G 718 X**

Revision Date: 22.05.2026 / Version 1.3 (GB)
Date of last issue: 17.04.2026
Print Date: 18.11.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: **WACKER® PRIMER G 718 X**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:
Industrial use. Professional use.
Intermediate chemical .

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor:	Wacker Chemie AG	
Street/POB-No.:	Gisela-Stein-Straße 1	
State/postal code/city:	D 81671 München	
Telephone:	+49 89 6279-0	
Contact point:	Wacker Chemicals Ltd.	
Street/POB-No.:	2 Arlington Square, Downshire Way	
Postal code/city:	Bracknell RG12 1WA	
Country:	United Kingdom	
Telephone:	+44 1344 401 670	
Information about the Safety Data Sheet:	Telephone	+49 8677 83-4888
	eMail	WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: **+44 1273 289451**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567):

Classification	H-Code
Flammable liquids, Category 2	H225
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity - single exposure, Category 3	H336

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567):

Pictogram(s):



Signal Word: Danger

H-Code	Hazard Statements
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

P-Code	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P261	Avoid breathing vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/ doctor if you feel unwell.

Hazard ingredients (labelling):
Acetone

Code	Additional Labelling
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

The product hydrolyses under formation of ethanol (CAS-Nr. 64-17-5). Ethanol is classified concerning both physical and health hazards. The hydrolysis rate and consequently the relevance for the hazard profile of the product is strongly dependent on the specific conditions.
Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

silane and siloxane with functional groups + auxiliary + solvent

3.2.2 Hazardous ingredients

Acetone			>80 – <90 %
CAS-No.: 67-64-1	EC-No.: 200-662-2	Index-No.: 606-001-00-8	
INHA [1], [2]	REACH No.: 01-2119471330-49		
Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567) *	Flam. Liq. 2 / H225; Eye Irrit. 2 / H319; STOT SE 3 / H336 EUH066		

Xylene, mixed isomers			>=1 – <3 %
CAS-No.: 1330-20-7	EC-No.: 215-535-7	Index-No.: 601-022-00-9	
INHA [1], [2]	REACH No.: 01-2119488216-32		
Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567) *	Eye Irrit. 2 / H319; STOT RE 2 / H373 (hearing organs); STOT SE 3 / H335; Asp. Tox. 1 / H304; Flam. Liq. 3 / H226; Acute Tox. 4, by inhalation / vapour / H332; Skin Irrit. 2 / H315; Acute Tox. 4, dermal / H312; Aquatic Chronic 3 / H412		

Triethoxyphenylsilane			>=1 – <3 %
CAS-No.: 780-69-8	EC-No.: 212-305-8		
INHA [1]	REACH No.: 01-2119969280-35		
Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567) *	Flam. Liq. 3 / H226; STOT RE 2 / H373 (Urinary bladder); Aquatic Chronic 3 / H412		

2,4-Pentanedione			<1 %
CAS-No.: 123-54-6	EC-No.: 204-634-0	Index-No.: 606-029-00-0	
INHA [1]	REACH No.: 01-2119458968-15		
Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567) *	Acute Tox. 3, by inhalation / vapour / H331; Acute Tox. 4, oral / H302; Flam. Liq. 3 / H226		

Type: INHA: ingredient, VERU: impurity

REACH registered substances may be included as impurities. These do not necessarily require identified uses and exposure scenarios in the safety data sheet.

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance; [5] = Endocrine disrupting properties

*For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:
In case of accident or if you feel unwell seek medical advice (show label or SDS where possible). Vapours may cause dizziness. Do not leave affected individuals unattended.

After contact with the eyes:
Rinse immediately with plenty of water for 10-15 minutes and seek medical advice.

After contact with the skin:
Wash with plenty of water or soap and water; immediately remove all contaminated clothing.

After inhalation:
Move to fresh air, keep the victim laying down and restful. If breathing has stopped, give artificial respiration.

After swallowing:
Seek medical advice immediately and produce the label or packaging. Do not induce vomiting. Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:
alcohol-resistant foam , carbon dioxide , sand , extinguishing powder .

Extinguishing media which must not be used for safety reasons:
water .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: toxic and very toxic fumes.

5.3 Advice for firefighters

Special protective equipment for fire fighting:
Use respiratory protection independent of recirculated air. Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:
Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

General information:

Avoid exposure by technical measures or personal protective equipment.

Precautions for safe handling:
Ensure adequate ventilation. Must be syphoned off in situ. Spilled substance increases risk of slipping. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:
Product may release ethanol. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:
Observe local/state/federal regulations.

Advice for storage of incompatible materials:
Observe local/state/federal regulations.

Further information for storage:
Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

Substance	Type	mg/m³	ppm	Dust fract.	Fibre/m³
Acetone	OEL	1810,0	750,0		
Acetone	EU	1210,0	500,0		
Xylene	OEL	441,0	100,0		
Xylene	EU	221,0	50,0		
Ethanol	OEL	1920,0	1000,0		

-

Xylene: the short-time value of the EU threshold is 442 mg/m3 (= 100 ppm); the substance can be absorbed by the skin.

Derived No-Effect Level (DNEL):

Acetone

Area of use**:**	Value**:**
Worker; by inhalation; local (acute)	2420 mg/m³
Worker; dermal; systemic (long term)	186 mg/kg bw/day
Worker; by inhalation; systemic (long term)	1210 mg/m³
Consumer; dermal; systemic (long term)	62 mg/kg bw/day
Consumer; oral; systemic (long term)	62 mg/kg bw/day
Consumer; by inhalation; systemic (long term)	200 mg/m³

2,4-Pentanedione

Area of use**:**	Value**:**
Worker; by inhalation; systemic (long term)	84 mg/m³
Worker; dermal; systemic (long term)	12 mg/kg bw/day
Consumer; oral; systemic (long term)	7 mg/kg bw/day

Triethoxyphenylsilane

Area of use:	Value:
Worker; dermal; systemic (long term) systemic (acute)	1,71 mg/kg/day
Worker; by inhalation; systemic (long term) systemic (acute)	49,5 mg/m³
Consumer; oral; systemic (long term)	0,84 mg/kg/day
Consumer; by inhalation; systemic (long term) systemic (acute)	12,1 mg/m³
Consumer; dermal; systemic (long term)	0,84 mg/kg/day

Xylene, mixed isomers

Area of use:	Value:
Worker; by inhalation; systemic (long term)	221 mg/m³
Worker; by inhalation; systemic (acute)	442 mg/m³
Worker; by inhalation; local (long term)	221 mg/m³
Worker; by inhalation; local (acute)	442 mg/m³
Worker; dermal; systemic (long term)	212 mg/kg bw/day
Consumer; by inhalation; systemic (long term)	65,3 mg/m³
Consumer; by inhalation; systemic (acute)	260 mg/m³
Consumer; by inhalation; local (long term)	65,3 mg/m³
Consumer; by inhalation; local (acute)	260 mg/m³
Consumer; dermal; systemic (long term)	125 mg/kg bw/day
Consumer; oral; systemic (long term)	2,5 mg/kg bw/day

Predicted No Effect Concentration (PNEC):

Acetone

Area of use:	Value:
freshwater	10,6 mg/l
marine water	1,06 mg/l
Intermittent release	21 mg/l
Sediment (freshwater)	30,4 mg/kg dry mass
Sediment (marine water)	3,04 mg/kg dry mass
sewage treatment plant	100 mg/l
Soil	29,5 mg/kg dry mass

2,4-Pentanedione

Area of use:	Value:
freshwater	0,2 mg/l
Intermittent release	0,26 mg/l
marine water	0,02 mg/l
Sediment (freshwater)	1,909 mg/kg dry mass
Sediment (marine water)	0,191 mg/kg dry mass
sewage treatment plant	1,32 mg/l
Soil	0,193 mg/kg dry mass

Triethoxyphenylsilane

Area of use:	Value:
freshwater	0,074 mg/l
marine water	0,0074 mg/l
Intermittent release	0,37 mg/l
Sediment (freshwater)	0,074 mg/kg wet weight The value was derived for the corresponding silanetriol (hydrolysis product).
Sediment (marine water)	0,0074 mg/kg wet weight The value was derived for the corresponding silanetriol (hydrolysis product).
Soil	0,022 mg/kg wet weight The value was derived for the corresponding silanetriol (hydrolysis product).

sewage treatment plant	100 mg/l

Xylene, mixed isomers

Area of use:	Value:
freshwater	0,044 mg/l
Intermittent release	0,01 mg/l
marine water	0,004 mg/l
Sediment (freshwater)	2,52 mg/kg dry mass
Sediment (marine water)	0,252 mg/kg dry mass
sewage treatment plant	1,6 mg/l
Soil	0,852 mg/kg dry mass

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:
Observe standard industrial hygiene practices for the handling of chemical substances. Do not inhale gases/vapours/aerosols. Use with adequate ventilation. Avoid contact with eyes and skin. Preventive skin protection recommended. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Provide emergency shower and eye-bath. Do not eat, drink or smoke when handling. Keep away from foodstuff, drink and feedingstuff.

Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

Personal protection equipment:

Respiratory protection

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

For long or intense exposure, use respiratory protective equipment. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

tight fitting protective goggles, according to acknowledged standards such as EN 166.

Hand protection

Protective gloves are required at all times when handling the material, according to recognized standards such as EN374.

Recommended glove types: Protective gloves made of butyl rubber
thickness of the material: > 0,7 mm
Breakthrough time: 10 - 30 min

Recommended glove types: Protective gloves made of 5-layer laminate of PE and EVOH (4H)
thickness of the material: > 0,062 mm
Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

Chemical protective clothing, according to acknowledged standards such as EN 13034, full-body liquid-tight protection if necessary, according to acknowledged standards such as EN 14605, if handled uncovered. Please observe the instructions regarding permeability time which are provided by the supplier. antistatic protective clothing, according to acknowledged standards such as EN 1149 and antistatic working shoes, according to acknowledged standards such as ISO 20345 and ISO 20347.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
Physical state	liquid	
Colour	orange	
Odour	pleasant	
Odour Threshold	no data available	
Melting point	not determined	
Boiling point/boiling range	56 °C at 1013 hPa	(not specified)
Lower explosion limit	1,2 Vol-%	(not specified)
Upper explosion limit	15 Vol-%	(not specified)
Flash point	-18 °C	(DIN 51755)
Ignition temperature	540 °C	(DIN 51794)
Thermal decomposition	exempt	
pH	Not applicable. Insoluble in water.	
Viscosity, kinematic	0,5 mm²/s at 25 °C	(not specified)
Water solubility	insoluble	
Partition coefficient: n-octanol/water	not applicable	
Vapour pressure	< 233 hPa at 20 °C	(not specified)
Density	0,82 g/cm³ (20 °C)	(DIN 51757)
Relative vapour density	no data available	
Particle Size Distribution	Not applicable.	

9.2 Other information

Hydrolysis products reduce the flash point. Explosion limits for released ethanol: 3.5 - 15%(V).

Property:	Value:	Method:
Sustained combustibility	not determined	
Evaporation rate	no data available	
Molecular weight	not applicable	

SECTION 10: Stability and reactivity

10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts with water, basic substances and acids. The reaction takes place with the formation of ethanol.

10.6 Hazardous decomposition products

Ethanol by hydrolysis. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 General information

Data derived for the product as a whole are of higher priority than data for single ingredients.

11.1.2 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE):
ATE_{mix} (dermal): > 2000 mg/kg
ATE_{mix} (by inhalation / vapour): > 20 mg/l/4 h
ATE_{mix} (Oral): > 2000 mg/kg

Data on substances:

Acetone:

Exposure routes	Result/Effect
Oral	LD50 5800 mg/kg Species: Rat, Sex: female, Method: OECD 401, Source: ECHA
dermal	LD50 > 15800 mg/kg Species: Rabbit, Sex: male, Source: ECHA
dermal	LD50 > 7426 mg/kg Species: Guinea pig, Sex: male, Source: ECHA
by inhalation (vapour)	LC50 132 mg/l / 55700 ppm; 3 h Species: Rat, Sex: male, Source: ECHA
by inhalation (vapour)	LC50 76 mg/l; 4 h Species: Rat, Sex: female, Source: ECHA

Xylene, mixed isomers:

Exposure routes	Result/Effect
Oral	LD50 3523 mg/kg Species: Rat, Sex: male, Method: OECD 401, Source: ECHA
Oral	LD50 > 4000 mg/kg Species: Rat, Sex: female, Method: OECD 401, Source: ECHA
dermal	LD50 > 4200 mg/kg Species: Rabbit, Sex: male, Source: ECHA
by inhalation (vapour)	LC50 27,6 mg/l / 6350 ppm; 4 h Species: Rat, Sex: male, Test substance: read-across substance, Method: OECD 403, Source: ECHA

11.1.3 Skin corrosion/irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

No skin irritation (Species: Rabbit, Source: ECHA)

Xylene, mixed isomers:

irritating (Species: Rabbit, Source: ECHA)

11.1.4 Serious eye damage/eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

irritating (Species: Rabbit, Method: OECD 405, Source: ECHA)

Xylene, mixed isomers:

mildly irritating (Species: Rabbit, Source: ECHA)

11.1.5 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

Exposure routes	Result
Skin contact	Does not cause skin sensitization. (Species: Guinea pig, Test system: Maximisation Test, Source: ECHA)

Xylene, mixed isomers:

Exposure routes	Result
Skin contact	Does not cause skin sensitization. (Species: Mouse, Test system: Local lymph node assay (LLNA), Method: OECD 429, Source: ECHA)

11.1.6 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

negative (Test system: chromosome aberration assay (in vitro) / mammalian cells, Method: OECD 473, Source: ECHA)
negative (Test system: mutation assay (in vitro) / bacterial cells, Method: OECD 471, Source: ECHA)
negative (Test system: mutation assay (in vitro) / mouse lymphoma cells, Method: OECD 476, Source: ECHA)
negative (Test system: micro nucleus assay (in vivo), Species: Mouse, Strain: B6C3F1, Sex: male and female, Application Route: Oral, Cell type: erythrocytes, Source: ECHA)

Xylene, mixed isomers:

negative (Test system: mutation assay (in vitro) / bacterial cells, Method: OECD 471, Source: ECHA)
negative (Test system: chromosome aberration assay (in vitro) / mammalian cells, Source: ECHA)
negative (Test system: mutation assay (in vitro) / yeast cells, Method: OECD 480, Source: ECHA)
negative (Test system: Rodent Dominant Lethal Test, Species: Mouse, Method: OECD 478, Source: ECHA)

11.1.7 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

Animal tests have not revealed any carcinogenic effects.

11.1.8 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances

Acetone:

Based on the available data the criteria for classification as toxic to reproduction are not fulfilled.

11.1.9 Specific target organ toxicity - single exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

Vapours may be narcotising.

Xylene, mixed isomers:

Vapours may be narcotising. Irritation of respiratory organs possible.

11.1.10 Specific target organ toxicity - repeated exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Acetone:

Result/Effect
NOAEC: 45 mg/l (Test system: Subchronic study, Species: Rat, Sex: male, Application Route: by inhalation, Route of administration: vapour, Test period: 56 d, Frequency of Treatment: 5 d/w, hours/day: 3, Subsequent observation period: 14 d, Source: ECHA)

11.1.11 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Xylene, mixed isomers:

Product can pose an aspiration hazard.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.2.2 Further toxicological information

None known.

Data on substances:

Product of hydrolysis (Ethanol):

Ethanol (64-17-5) is readily absorbed at all exposure routes. Ethanol may cause irritation of eyes and mucosa, trigger dysfunction of the central nervous system and cause nausea as well as dizziness. Chronic exposure to high amounts of ethanol may cause damage to liver and central nervous system.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

No expected damaging effects to aquatic organisms.

12.2 Persistence and degradability

Assessment:

Organic solvent: readily biologically degradable. Silicone content: biologically not degradable. Elimination by adsorption to activated sludge.

Data on substances:

Product of hydrolysis (Ethanol):

Ethanol is readily biodegradable.

12.3 Bioaccumulative potential

Assessment:

No data known.

12.4 Mobility in soil

Assessment:

No data known.

12.5 Results of PBT and vPvB assessment

PBT assessment
No data available.

vPvB Assessment
No data available.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

none known

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:
Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:
Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	UN1993
RID	UN1993
IMDG	UN1993
ICAO/IATA	UN1993

14.2 Proper shipping name

ADR	Entzündbarer flüssiger Stoff, n.a.g. (Aceton, Triethoxymethylsilan)
ADR (Domestic transport regulations)	Flammable liquid, n.o.s (acetone, triethoxymethylsilane)
RID	Entzündbarer flüssiger Stoff, n.a.g. (Aceton, Triethoxymethylsilan)
RID (Domestic transport regulations)	Flammable liquid, n.o.s (acetone, triethoxymethylsilane)
IMDG	Flammable liquid, n.o.s. (acetone, triethoxymethylsilane)
ICAO/IATA	Flammable liquid, n.o.s. (acetone, triethoxymethylsilane)

14.3 Transport hazard class

ADR	3 (Limited quantity (LQ): 1L)
RID	3
IMDG	3
ICAO/IATA	3

14.4 Packing group

ADR	II
RID	II
IMDG	II
ICAO/IATA	II

14.5 Environmental hazards

Environmentally hazardous: no
Marine pollutant (IMDG): no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Maritime transport in bulk according to IMO instruments

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Control of Major Accident Hazards Regulations 2015 (COMAH)

Listed in Directive	Ser. number in list	Qualifying Quantity 1	Qualifying Quantity 2
FLAMMABLE LIQUIDS	P5c	5.000 t	50.000 t

Relevant regulations:
SI 2002/1689: CHIP Regulations 2002
SI 2002/2677: COSHH Regulations 2002
SI 1999/3242: Management of Health & Safety at Work Regulations 1999
Health & Safety at Work Act 1974
SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.
Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

Other specifications, restrictions and prohibitions:

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors - ANNEX II. REPORTABLE EXPLOSIVES PRECURSORS: Banned and/or restricted

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors - ANNEX I. RESTRICTED EXPLOSIVES PRECURSORS: Not applicable

REACh Annex XVII: For this product, entry 3 of Annex XVII to Regulation 1907/2006, as amended, must be taken into account.

Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan ..... : **ENCS** (Handbook of Existing and New Chemical Substances):
This product is listed in, or complies with, the substance inventory.

Australia ..... : **AIIC** (Australian Inventory of Industrial Chemicals):
This product is listed in, or complies with, the substance inventory.

China..... : **IECSC** (Inventory of Existing Chemical Substances in China):
This product is listed in, or complies with, the substance inventory.

Canada ..... : **DSL** (Domestic Substance List):
This product is listed in, or complies with, the substance inventory.

Philippines..... : **PICCS** (Philippine Inventory of Chemicals and Chemical Substances):
This product is listed in, or complies with, the substance inventory.

United States of America (USA)..... : **TSCA** (Toxic Substance Control Act Chemical Substance Inventory):
All components of this product are listed as active or are in compliance with the substance inventory.

Taiwan ..... :	**TCSI** (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA)..... :	**REACH** (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea) ..... :	**AREC** (Act on Registration and Evaluation of Chemicals; “K-REACH”): Please approach your regular contact for more detailed information.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Key or legend to abbreviations and acronyms used in the safety data sheet

ABEK - Multi-Range Filter A, B, E, K; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; APF - Assigned Protection Factor; CAS No. - Chemical Abstracts Service Registry Number; DFG - German Research Foundation; DIN - German institute for standardization; DOC - Dissolved Organic Carbon; d/w - days per week; EC / CE / EG - European Community; EC50 / CE50 - Median effective concentration; ECHA - European Chemicals Agency; ED - endocrine disruptor; EG-RL - test method according to Regulation 440/2008; EN - European Standard; ERC - Environmental Release Category; g/cm³ - gram per cubic centimeter; h - hour(s); H-Code - hazard statement code(s); hPa - Hectopascal; IATA Regs - International Air Transport Association (IATA) Dangerous Goods Regulations;IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk;IC50 / CI50 - half maximal inhibitory concentration;IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IMDG Code - International Maritime Dangerous Goods Code; ISO - International Organization for Standardization; LC50 / CL50 - medium lethal concentration; LD50 / DL50 - medium lethal dose; LOAEC - Lowest Observed Adverse Effect Concentration; LOAEL - Lowest Observed Adverse Effect Level; MARPOL - International Convention for the Prevention of Marine Pollution from Ships; mg/g - milligrams per gram; mg/kg - milligrams per kilogram; mg/l - milligrams per liter; mg/m³ - milligrams per cubic meter; min - minutes; mJ - millijoule; mm - millimeter; mm²/s - square millimeter per second; mPa.s - Millipascal second(s); MSDS / SDB / SDS - safety data sheet; No Observed Adverse Effect Concentration; NOAEL - No Observed adverse effect level; NOEC - No Observed Effect Concentration; NOEL - No Observed Effect Level; OECD - Organization for Economic Cooperation and Development; PBT - persistent, bioaccumulative, toxic; PC - product category; P-Code - precautionary statement code(s); ppm - parts per million; PROC - process category; RCP - reciprocal calculation-based procedure; RID - convention concerning international carriage by rail; SU -

sector of use; SVHC - substance of very high concern; Vol% - volume percent; UN No. - United Nations Dangerous Goods Number; vPvB - very Persistent, very Bioaccumulative

Full text of H-Statements:

Flam. Liq. 2; H225	:	Flammable liquids Category 2; Highly flammable liquid and vapour.
Eye Irrit. 2; H319	:	Serious eye damage/eye irritation Category 2; Causes serious eye irritation.
STOT SE 3; H336	:	Specific target organ toxicity - single exposure Category 3; May cause drowsiness or dizziness.
EUH066	:	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2; H319	:	Serious eye damage/eye irritation Category 2; Causes serious eye irritation.
STOT RE 2; H373	:	Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through prolonged or repeated exposure.
STOT SE 3; H335	:	Specific target organ toxicity - single exposure Category 3; May cause respiratory irritation.
Asp. Tox. 1; H304	:	Aspiration hazard Category 1; May be fatal if swallowed and enters airways.
Flam. Liq. 3; H226	:	Flammable liquids Category 3; Flammable liquid and vapour.
Acute Tox. 4; H332	:	Acute toxicity Category 4; Harmful if inhaled.
Skin Irrit. 2; H315	:	Skin corrosion/irritation Category 2; Causes skin irritation.
Acute Tox. 4; H312	:	Acute toxicity Category 4; Harmful in contact with skin.
Aquatic Chronic 3; H412	:	Long-term (chronic) aquatic hazard Category 3; Harmful to aquatic life with long lasting effects.
Flam. Liq. 3; H226	:	Flammable liquids Category 3; Flammable liquid and vapour.
STOT RE 2; H373	:	Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through prolonged or repeated exposure.
Aquatic Chronic 3; H412	:	Long-term (chronic) aquatic hazard Category 3; Harmful to aquatic life with long lasting effects.
Acute Tox. 3; H331	:	Acute toxicity Category 3; Toxic if inhaled.
Acute Tox. 4; H302	:	Acute toxicity Category 4; Harmful if swallowed.
Flam. Liq. 3; H226	:	Flammable liquids Category 3; Flammable liquid and vapour.

Classification	Rationale:
Flammable liquids, Category 2	On basis of test data.
Serious eye damage/eye irritation, Category 2	Calculation method
Specific target organ toxicity - single exposure, Category 3	Calculation method

- End of Safety Data Sheet -